

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

Three Piece Automobile Wheel

Abstract

5 The three piece automobile wheel is provided with an inner rim, an
outer rim, and a center disc. The center disc is attached to a flange section of
the inner rim and outer rim. A trough is established in the inner rim between
the flange section and rim flange. The outer side-wall of the trough nearest
10 the flange section is disposed off the rim center-plane towards the center
disc, a valve opening passes through the outer side-wall for valve attachment,
and the configuration allows the valve base to be disposed inside the trough.
The center disc is provided with a through-hole region to expose the valve
stem to the outside.